

Special Purpose - Border Boxing

Images may include options.

Atlanta Attachment 1947BX6

Border Boxing

- Operator friendly
- Cord width size is quickly adjusted with a release pin
- Left folder is fixed, only need to move the right folder, one needle and one looper thread
- Folders easily slide out on a drawer type rail system to allow access to sewing components
- Folder assembly is easily removed for sewing head maintenance, timing, etc
- Independent stepper driven puller allows for push button increases or decreases in material stretch
- Optional photocell controlled cutter is integral to the sewing unit and easily adjustable
- Efka servo motor drive system



Technical Information



- Multi needle
- Double chainstitch
- Bottom feed and top puller
- Looper, cross-line
- Automatic presser footlift
- Needle thread monitor

SPECIFICATIONS	
Max sewing speed (rpm)	2400
Factory preset speed (rpm)	2000
Max stitch length (spi)	6-7
Max needle distance (inch)	6
Needle system	62 x 57
Needle size	18/100
Weight of material	MEDIUM
Max presser footlift (inch)	3/8
Voltage (v/ph/hz)	220V 1PH 60HZ
Current (amps)	5
Motor type	EFGA DC
Air pressure (psi)	80
Air consumption (cfm)	1
Shipping weight (lbs)	980
Shipping dimensions (w/l/h, inch)	60 x 48 x 55

www.atlatt.com • sales@atlatt.com



Atlanta Attachment Company

The Company that
Sudden Service
built

PATENTS: Our equipment may be covered by one or more patents.
Please go to the following web page for an up-to-date patent list: www.atlatt.com/patents
© 2018 Atlanta Attachment Co. 18044062618

362 Industrial Park Drive
Lawrenceville, GA 30046
+1 (770) 963-7369 • FAX +1 (770) 963-7641