Images may include options.

Border Boxing

- Multi-needle Chainstitch with 2”-6” sewing capacity at 1/4” increments
- Dual Puller System - First Puller synchronized with sewing head; Second puller variable allowing for the finished cording not to be pulled
- Folder and Feed components easily adjustable. Dedicated sized machines are not required
- Folder assembly is removable for easy access to sewing head
- Flexible Pedal Setup







Technical Information

SPECIFICATIONS	
Max sewing speed (rpm)	2400
Factory preset speed (rpm)	2000
Max stitch length (spi)	6-7
Max needle distance (inch)	6
Needle system	62 x 57
Needle size	18/100
Weight of material	MEDIUM
Max presser footlift (inch)	3/8
Voltage (v/ph/hz)	220V 1PH 60HZ
Current (amps)	5
Motor type	EFKA DC
Air pressure (psi)	80
Air consumption (cfm)	1
Shipping weight (lbs)	980
Shipping dimensions (w/l/h, inch)	60 x 48 x 55

Options

- Border Cutting system utilizing adjustable photocell

PATENTS: Our equipment may be covered by one or more patents.
Please go to the following web page for an up-to-date patent list: www.atlatt.com/patents
© 2019 Atlanta Attachment Co. 18054070719

362 Industrial Park Drive
Lawrenceville, GA 30046
+1 (770) 963-7369

Atlanta Attachment Company
a Division of HSM